

DTX-1800 / DSX-5000 / DSX-8000

	DTX-1800 CableAnalyzer™	DSX-5000 CableAnalyzer™	DSX-8000 CableAnalyzer™
Category 6A / Class EA	22 seconds	10 seconds	8 seconds
Category 8 / Class I/II test time	x	x	15 seconds
Advanced Diagnostics		Yes	Yes
Touch screen	No	Capacitive with gestures	Capacitive with gestures
Setup multiple tests in advance	No	ProjX™	ProjX™
IEC 61935-1 Ed.4 Level V Accuracy	No	Yes	Yes
Level VI/2G Accuracy (2 GHz)	No	No	Yes
Channel Adapter	500 MHz Range	1 GHz Range	2 GHz Range
Permanent Link Adapter	500 MHz Range	1 GHz Range	2 GHz Range
Resistance Unbalance	No	Yes	Yes
TCL measurement	No	Yes	Yes
ELTCTL measurement	No	Yes	Yes
Shield integrity check	No	Yes	Yes
Built in Alien Xtalk module	No	Yes	Yes
Internal memory	Up to 250 graphical Cat 6 test	≈ 12,000 Cat 6A with plots	≈ 12,000 Cat 6A with plots
Supported by LinkWare Live SaaS	No	Yes	Yes
Supported by LinkWare PC	Yes	Yes	Yes